

ACDelco Coolant

ACDELCO DEX-COOL IS AN EXTENDED LIFE AUTOMOTIVE ENGINE COOLANT AND ANTI-FREEZE PROVIDING UP TO 5 YEARS PROTECTION.

FEATURES & BENEFITS:

- Provides effective, long term corrosion protection for aluminum, brass, cast iron, steel, solder and copper.
- 5 year or 240,000 km recommended service interval when complete flush and fill is performed.
- Protects against winter freeze up and minimizes the chance of summer boil over.
- Compatible with water pump seal materials and minimizes the formation of abrasive dissolved solids.
- No silicate dropout or gel formation during use or storage.
- Biodegradable in its pure unused form.
- Excellent heat transfer properties.
- Nitrite, borate, phosphate, nitrate, and amine free.
- Outstanding hot surface aluminum protection.
- Provides protection in high operating temperatures.
- Compatible with conventional antifreeze.



ACDELCO ALL SEASONS ANTIFREEZE / COOLANT INHIBITOR SUITABLE FOR BOTH PETROL AND HEAVY-DUTY DIESEL ENGINES.

FEATURES & BENEFITS:

- Formula suits both automotive and heavy-duty diesel engines.
- Formulated with anti-foam characteristics, aluminum corrosion protection and heat transfer properties.
- Provides corrosion protection for aluminum, brass, copper, solder, steel and cast iron.
- Compatible with cooling system filters and most major brands of coolant.
- Biodegradable in its pure unused form.
- Mixes readily with clean tap water.



ACDelco offers a comprehensive Product Range to suit Most Makes & Models.

For your nearest ACDelco Automotive Parts Stockist call 1800 ACDelco

1800 ACDelco
acdelco.com.au

ACDelco

ACDelco Coolant

ACDELCO DEX-COOL:

PACK SIZE

Part Number: **92147598** - 1 Litre
Part Number: **92145527** - 5 Litres
Part Number: **95710438** - 20 Litres

SPECIFICATIONS

GM 6277M
ASTM D 4986
ASTM D 3306

APPLICATIONS

ACDelco DEX-COOL® ANTIFREEZE/COOLANT is recommended for use in the cooling systems of automotive engines. This product meets ASTM D 3306 for automotive service and ASTM D 4985 for heavy duty diesel service.

TYPICAL CHARACTERISTICS

Appearance: Red
Specific gravity 60/60 °F: 1.130
Freezing point, °F (ASTM D 1177) 50 vol. % q.s. aqueous solution: -34
pH (ASTM D 1287), 1:2 dilution with water: 8.3
Reserve Alkalinity(ASTM D 1121), as received 10 ml sample: 6.0
Silicate, % (as Anhydrous Alkali Metasilicate): None



ACDELCO ALL SEASONS ANTIFREEZE / COOLANT INHIBITOR:

PACK SIZE

Part Number: **92140054** - 1 Litre
Part Number: **92140057** - 5 Litres
Part Number: **92140055** - 20 Litres

SPECIFICATIONS

AAMVA
General Motors GM1899M
J.I. Case JIC501
Cummins 90T8-4
PACCAR
Ford ESE-M97B44-A
Freightliner
ASTM D 3306 incl. D 4340
Chrysler MS-7170
John Deere H24C1
Federal Specification A-A-870
TMC of ATA RP-302A



General Motors GM1825M
ASTM D 4985
John Deere H24B1
Detroit Diesel Corp.
SAE J1034
Mack Truck

APPLICATIONS

This product is suitable for use in industrial internal combustion engines where an antifreeze/coolant is required to provide protection against freezing, boil over, and corrosion.

TYPICAL CHARACTERISTICS

Appearance: Fluorescent Green
Specific gravity 60/60 iF: 1.130
Freezing point, °F (ASTM D 1177) 50% vol, q.s. aqueous solution: -34
pH (ASTM D 1287), 1:2 dilution with water: 10.5
Reserve Alkalinity (ASTM D 1121), as received: 12.0
Silicate, % (as Anhydrous Alkali Metasilicate): 0.09

For further details refer to the ACDelco website www.acdelco.com.au

Available From:

1800 ACDelco
acdelco.com.au

ACDelco®